



**Super Silent version**

**DESCRIPTIVE**

- Connection terminal box rental type
- Retention bund
- Primary fuel filter
- Four-pole circuit breaker
- Oil drainage pump
- Dusty atmosphere air filter
- Battery isolating switch
- 3 tracks valve
- Special rental soundproofed container

**POWER DEFINITION**

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

**TERMS OF USE**

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

**ASSOCIATED UNCERTAINTY**

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

**R1500**

Engine ref.	KD36V16-5CEP
Alternator ref.	KH05520T
Performance class	G3

**GENERAL CHARACTERISTICS**

Frequency (Hz)	50 Hz
Voltage (V)	400/230

Standard Control Panel	APM403
------------------------	--------

**DIMENSION/ SILENT SOUND LEVEL**

Type soundproofing	CIR20 SSi DRY
Length (mm)	6058
Width (mm)	2438
Height (mm)	2591
Dry weight (kg)	16100
Tank capacity (L)	1850
Autonomy @ 75% of load (h)	7,20
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP) #Incert_lb_2_1#	79
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP) #Incert_lb_2_2#	70
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	100



# R1500

## ENGINE CHARACTERISTICS

### GENERAL ENGINE DATAS

Engine brand	KOHLER KD Series
Engine ref.	KD36V16-5CEP
Air inlet system	Turbo
Cylinders configuration	V
Number of cylinders	16
Displacement (L)	35,96
Charge Air coolant	Air/Air
Bore (mm) x Stroke (mm)	135 x 157
Compression ratio	15 : 1
Speed (RPM)	1500
Pistons speed (m/s)	7,85
Maximum stand-by power at rated RPM (kW)	1333
Frequency regulation, steady state (%) +/-	0.25%
BMEP @ PRP 50 Hz (bar)	27
Governor type	Electronic

### COOLING SYSTEM

Radiator & Engine capacity (L)	255
Fan power (kW)	40
Fan air flow w/o restriction (m3/s)	20,50
Available restriction on air flow (mm H2O)	25
Type of coolant	Gencool

### EMISSIONS

Emission PM (g/kW.h)	
Emission CO (g/kW.h)	
Emission HC+NOx (g/kWh)	0
Emission HC (g/kW.h)	

### EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	537
Exhaust gas flow @ ESP 50Hz (L/s)	3586
Max. exhaust back pressure (mm H2O)	850

### FUEL

Consumption @ 100% load ESP (L/h)	305,80
Consumption @ 100% PRP load (L/h)	278
Consumption @ 75% PRP load (L/h)	222,40
Consumption @ 50% PRP load (L/h)	149,70
Maximum fuel pump flow (L/h)	263

### OIL

Oil system capacity including filters (L)	152
Min. oil pressure (bar)	3,30
Max. oil pressure (bar)	
Oil consumption 100% ESP 50Hz (L/h)	0,16
Oil sump capacity (L)	135

### HEAT BALANCE


Heat rejection to exhaust (kW)	852
Radiated heat to ambient (kW)	85
Heat rejection to coolant HT (kW)	433

### AIR INTAKE

Max. intake restriction (mm H2O)	500
Intake air flow (L/s)	1177

Alternator ref.	KH05520T	Continuous Nominal Rating 40°C (kVA)	1358
Number of Phase	Three phase	Standby Rating 27°C (kVA)	1474,40
Power factor (Cos Phi)	0,80	Efficiencies 100% of load (%)	96,20
Altitude (m)	0 à 1000	Air flow (m3/s)	1,50
Overspeed (rpm)	2250	Short circuit ratio (Kcc)	0,2990
Number of pole	4	Direct axis synchro reactance unsaturated (Xd) (%)	348,50
Capacity for maintaining short circuit at 3 In for 10 s	Yes	Quadra axis synchro reactance unsaturated (Xq) (%)	116,70
Insulation class	H	Open circuit time constant (T'do) (ms)	9500
T° class (H/125°), continuous 40°C	H / 125°K	Direct axis transient reactance saturated (X'd) (%)	14,60
T° class (H/163°C), standby 27°C	H / 163°K	Short circuit transient time constant (T'd) (ms)	310
AVR Regulation	Yes	Direct axis subtranscient reactance saturated (X''d) (%)	6,90
Total Harmonic Distortion in no-load DHT (%)	2,6	Subtranscient time constant (T''d) (ms)	22
Total Harmonic Distortion, on linear load DHT (%)	1,7	Quadra axis subtranscient reactance saturated (X''q) (%)	15,33
Wave form : NEMA=TIF	<40	Subtranscient time constant (T''q) (ms)	22
Wave form : CEI=FHT	<2	Zero sequence reactance unsaturated (Xo) (%)	3,63
Number of bearing	Single Bearing	Negative sequence reactance saturated (X2) (%)	9,63
Coupling	Direct	Armature time constant (Ta) (ms)	32
Voltage regulation at established rating (+/- %)	0,50	No load excitation current (io) (A)	0,79
Recovery time (Delta U = 20% transient) (ms)	200	Full load excitation current (ic) (A)	3,28
Indication of protection	IP 23	Full load excitation voltage (uc) (V)	35,40
Technology	Brushless	Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	3657,50
		Transient dip (4/4 load) - PF : 0,8 AR (%)	14,15
		No load losses (W)	18970
		Heat rejection (W)	44075,1
			0
		Unbalanced load acceptance ratio (%)	100

APM403, basic generating set and power plant control



The APM403 is a versatile control unit which allows operation in manual or automatic mode  
Measurements : voltage and current  
kW/kWh/kVA power meters  
Standard specifications: Voltmeter, Frequency meter.  
Optional : Battery ammeter.  
J1939 CAN ECU engine control  
Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.  
Engine parameters: Fuel level, hour counter, battery voltage.  
Optional (standard at 24V): Oil pressure, water temperature.  
Event log/ Management of the last 300 genset events.  
Mains and genset protection  
Clock management  
USB connections, USB Host and PC,  
Communications : RS485 INTERFACE  
ModBUS protocol /SNMP  
Optional : Ethernet, GPRS, remote control, 3G, 4G,  
Websupervisor, SMS, E-mails