Industrial Generator Set - D630



Ratings Range

400/230 V - 50 Hz

Standby	**kW**	504
	kVA	630
Prime	**kW**	458
	kVA	573

Benefits and features

Rehlko premium quality
- Design offices using the latest technical innovations
- Modern fully certified factories
- A cutting edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested

Rehlko premium performances
- Optimized and certified sound levels
- Reliable power, even in extreme conditions
- Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- Robust base frames and high-quality enclosures
- Protection of installations and people
- Approved in line with the most stringent standards

Engines
- Premium level engines, in-house or from strong partners
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

Alternator
- Provide industry leading motor starting capability
- Made in Europe
- Built with a class H insulation and IP23

Cooling
- A compact and complete solution using a mechanically driven radiator fan
- Designed or optimized by Rehlko
- High temperature and altitude product capacity available

Base frame and enclosure
- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1000 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and
- connection of the generator
- Robust design optimized for transportation

General Specifications

Manufacturer	Rehlko
Engine ref.	DP180LA
Alternator choices	KH02713T KH02954T
Performance class	G3
Controllers	APM303 APM403 Terminal block M80
Consumption @ 100% load ESP (L/h)*	134
Consumption @ 100% load PRP (L/h)*	123
Emission level	Fuel consumption optimization
Type of Cooling	Radiator
Factory installed enclosures	M240 M240-DW

"* Volumetric Fuel consumption is up to 4% higher when using HVO than Diesel Fuel"

Generator sets ratings

		Standby rating			Prime rating	
	Hz	kWe	kVA	Amps	kWe	kVA
400/230	50	504	630	909	458	573
380/220	50	504	630	957	458	573
200/115	50	504	630	1819	458	573
240 TRI	50	504	630	1516	458	573
230 TRI	50	504	630	1581	458	573
415/240	50	504	630	876	458	573

Engine Specifications	
Engine brand	Hyundai
Engine ref.	DP180LA*
Air inlet system	Turbo
Cylinder configuration	10 - V
Displacement (l)	18,27
Bore (mm) x Stroke (mm)	128 x 142
Compression ratio	15 : 1
Speed 50Hz (RPM)	1500
Maximum stand-by power at rated RPM (kW)	552
Governor type	Electronic
Frequency regulation, steady state (%)	+/- 0.25%

Lubrication System	
Oil Filter Quantity and type****	
Charge Air coolant	Air/Air

*****Rehlko recommends the use of genuine oil and filters.*

Fuel System	
Maximum fuel pump flow (l/h)	540
Max head on fuel return line (m fuel)	1
Fuel	Diesel Fuel

* Engine reference may be partially modified depending on genset application, options selected by the customer and lead time required.

Consumption with cooling system	
Fuel consumption @ ESP Max Power (l/h)	135,4
Fuel consumption @ PRP Max Power (l/h)	123,6
Fuel consumption @ 75% of PRP Power (l/h)	94,2
Fuel consumption @ 50% of PRP Power (l/h)	64,8

Cooling system	
Radiator & Engine capacity (l)	112
Fan power 50Hz (kW)	16
Fan air flow w/o restriction (m3/s)	10,5
Available restriction on air flow (mm H2O)	20
Free	Glycol-Ethylene
Radiated heat to ambiant (kW)	52
Heat rejection to coolant HT (kW)	243
Coolant capacity HT, engine only (l)	21
Max coolant temperature, Shutdown (°C)	103
Thermostat begin of opening HT (°C)	71
Thermostat end of opening HT (°C)	85

Exhaust system	
Heat rejection to exhaust (kW)	508
Exhaust gas temperature @ ESP (°C)	562
Exhaust gas flow @ ESP (l/s)	1767
Electrical system	
Battery voltage (V)	24
Air Intake system	
Combustion air flow (l/s)	553
Radiated heat to ambiant (kW)	52

Alternator Specifications	
Number of pole	4
Technology	Brushless
AVR Regulation	Yes
Insulation class	H
Indication of protection	IP23
Number of bearing	1
Number of wires	12
Coupling	Direct
Overspeed (rpm)	2250
Voltage regulation at established rating (+/- %)	0,5
Unbalanced load acceptance ratio (%)	8

Alternator standard features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof constructio
- Superior voltage waveform

Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.



Basic terminal block
It is used as a basic terminal block for connecting a control unit. Offers the following functions:
- emergency stop button
- customer connection terminal block
- CE certified



M80 controller
The M80 is a dual-function control panel. It can be used as a basic terminal block for connecting a control unit and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters. Offers the following functions:
- Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator
- emergency stop button
- customer connection terminal block
- CE certified



APM303 controller
The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:
- Measurements: phase-to-neutral and phase-to-phase voltages, fuel level (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)
- Supervision: Modbus RTU communication on RS485
- Reports: (In option : 2 configurable reports)
- Safety features: Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency (Maximum active power P<66kVA)
- Traceability: Stack of 12 stored events

For further information, please refer to the data sheet for the APM303



APM403 controller
The APM403 is a versatile control unit which allows operation in manual or automatic mode
- Measurements : voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional : Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.

Codes and Standards

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:
- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

Power ratings definition according to ISO8528-1 (2018-02 edition) and ISO-3046-1

Emergency Standby Power (ESP): The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <70%.
Prime Power (PRP): At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <70%.

Warranty informations

Standard warranty period:
- for Products in "back-up" service
  - 36 months from the date the Product leaves the plant
  - 24 months from the Product’s commissioning date
  - 1,000 running hours

The warranty expires when one of the above conditions is met.
- for Products in “prime” or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
  - 24 months from the date the Product leaves the plant
  - 12 months from the Product’s commissioning date
  - 2,500 running hours

The warranty expires when one of the above conditions is met.
For more details regarding conditions of application and scope of the warranty please refer to our General “terms & conditions of sales”.

Standard scope of supply

All our gensets are fitted with:
- Industrial water cooled DIESEL engine
- Electric starter & charge alternator
- Standard air filter
- Schneider or ABB electric circuit breaker, adapted to the short-circuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- 4 lifting points on the chassis, lifting bar on the top included from 165 kVA ESP or optional
- highly durable QUALICOAT certified epoxy paint
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- IP 64 locks, made from stainless materials
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 110 kVA ESP
- Charged DC starting battery with electrolyte
- Emergency stop button on the outside
- Flexible fuel lines & lub oil drain cock
- Exhaust outlet with flexible and flanges
- User’s manual (1 copy)

Excluded from the supply:
- For XPRESS products, from 25 to 1500 kVA: oil and antifreeze liquid

- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 genset events.
- Mains and genset protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G
- Websupervisor, SMS, E-mails

Dimensions and Weights





Tank capacity (L)	Overall Size, max., L x W x H, (mm)			Dry weight (kg)	Sound levels		
	Length (mm)	Width (mm)	Height (mm)		Sound power level guaranteed (Lwa) 50Hz (75% PRP)	Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)
Dimensions compact version – Radiator							
745	3620	1900	1944	3893			
M240 - Dimensions soundproofed version – Radiator							
745	5320	2071	2658	5683	107	87	77
Dimensions DW compact version – Radiator							
2420	5367	2153	2219	4871			
M240 - Dimensions DW soundproofed version – Radiator							
2420	5367	2153	2933	6589	107	87	77

** dimensions and weight without options*

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.
Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.