



Ratings Range

400/230 V - 50 Hz

Standby kW 2000 kVA 2500

Prime kW 1818

kVA 2273



Benefits and features

Rehlko premium quality

- Rehlko provides one source responsibility for the generating set and accessories
- The generator set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested
- The generator sets are designed in accordance to ISO8528
- Approved for use with HVO (Hydrotreated Vegetable Oil) according to EN15940

Rehlko premium performances Engines

- High reliability enhanced through a simple design for optimal functional performances
- High performances turbochargers providing high engine performances under all loads
- Easy operation and maintenance: accessories requiring daily maintenance are conveniently located on the same side of the engine

Alternator

- · Provide industry leading motor starting capability
- Excitation system to permit sustained overcurrent > 300% In, during 10 sec
- Built with a class H insulation and IP23

Cooling

- A compact and complete solution using a mechanical or an electrical radiator fan (depending of genset type)
- High temperature and altitude product capacity available **Control panel**
- The Rehlko wide controller range provides the reliability and performances you expect from your equipment. You can program, manage and diagnose it easily and in an efficient way

Rehlko worldwide support

- A standard two-year or 1000-hours limited warranty for standby applications.
- A standard one-year or 2500 hours limited warranty for prime power applications.
- A worldwide product support

Generator sets ratings

		Standby rating			Prime rating	
	Hz	kWe	kVA	Amps	kWe	kVA
400/230	50	2000	2500	3609	1818	2273
415/240	50	2000	2500	3478	1818	2273

General Specifications

Manufacturer	Rehlko
Engine ref.	S16R2-PTAW
Alternator choices	KH05793T
	KH06931T
Performance class	G3

Voltage (V) 400/230 415/240 Controllers Terminal block M80 APM403

APM802

Consumption @ 100% load ESP (L/h)* 528 Consumption @ 100% load PRP (L/h)* 476

Emission level Fuel consumption optimization

May Pote Contar Continuous (DCC) Poting 2500 kVA


Max. Data Center Continuous (DCC) Rating

2000 kWe
Type of Cooling

Factory installed enclosures

"* Volumetric Fuel consumption is up to 4% higher when using HVO than

V01E_T2500-04_2025-11-02 1/6






time required.

Engine Specifications		Consumption with cooling system		
Engine brand	MITSUBISHI	Specific consumption @ ESP Max Power (g/kW.h)	208	
Engine ref.	S16R2-PTAW*	Specific consumption @ PRP Max Power (g/kW.h)	206	
Air inlet system	Turbo	Specific consumption @ 75% of PRP Power	202	
Cylinder configuration	16 - V	(g/kW.h) Specific consumption @ 50% of PRP Power	207	
Displacement (I)	79,9	(g/kW.h)		
Bore (mm) x Stroke (mm)	170 x 220	Cooling system (HT/LT)		
Compression ratio	14:1	Radiator & Engine capacity (I)	567	
Speed 50Hz (RPM)	1500	Fan power 50Hz (kW)	61	
Maximum stand-by power at	2167	Fan air flow w/o restriction (m3/s)	36	
rated RPM (kW) Governor type	Electronic	Available restriction on air flow (mm H2O)	20	
Frequency regulation, steady		Type of coolant	Glycol-Ethyler	
state (%)	+/- 0.25%	Radiated heat to ambiant (kW)	168	
Lubrication System		Heat rejection to coolant HT (kW)	668	
Oil Filter Quantity and type****		Coolant capacity HT, engine only (I)	157	
Charge Air coolant	Water/Air + Water/Air	Outlet coolant temperature (°C)	95	
****Rehlko recommends the use of genuine oil and filters.		Max coolant temperature, Shutdown (°C)	98	
		Max. pressure at inlet of HT water pump (mbar)	981	
Fuel System Maximum fuel pump flow (I/h)		Thermostat begin of opening HT (°C)	71	
Max head on fuel return line (m	2	Thermostat end of opening HT (°C)	85	
fuel)	2	, ,		
Fuel	Diesel Fuel/HVO			
* Engine reference may be partial genset application, options select	,	Coolant capacity LT, engine only (I)	33	

V01E_T2500-04_2025-11-02 2 / 6





Exhaust system	
Heat rejection to exhaust (kW)	1355
Exhaust gas temperature @ ESP (°C)	
Exhaust gas flow @ ESP (I/s)	8434
Electrical system	
Battery voltage (V)	24
Air Intake system	
Combustion air flow (I/s)	2800
Radiated heat to ambiant (kW)	168

Alternator Specifications				
Number of pole	4			
Technology	Brushless			
AVR Regulation	Yes			
Insulation class	Н			
Indication of protection	IP23			
Number of bearing	1			
Number of wires	06			
Coupling	Direct			
Overspeed (rpm)	2250			
Voltage regulation at established rating (+/- %)	0,5			
Unbalanced load acceptance ratio (%)	8			

Alternator standard features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds
- Superior voltage waveform

Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.

V01E_T2500-04_2025-11-02 3/6





Basic terminal block

It is used as a basic terminal block for connecting a control unit. Offers the following functions:

- emergency stop button
- customer connection terminal block
- CE certified



M80 controller

The M80 is a dual-function control panel. It can be used as a basic terminal block for connecting a control unit and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters. Offers the following functions:

- Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator
- · emergency stop button
- · customer connection terminal block
- CE certified



APM403 controller

The APM403 is a versatile control unit which allows operation in manual or automatic mode

- Measurements: voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional: Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.
- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 genset events.
- · Mains and genset protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G
- Websupervisor, SMS, E-mails



APM802 controller

Advanced power plant management control

Dedicated to power plant management APM802 provides advanced control, system monitoring, and system diagnostics for optimum performance and compatibility

· Graphic display with touchscreen

Codes and Standards

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

Power ratings definition according to ISO8528-1

(2018-02 edition) and ISO-3046-1

Emergency Standby Power (ESP): The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <80%.

Prime Power (PRP): At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <80%.

Data Center Mission Critical (DCP): Data Center Mission Critical power is defined as being the maximum power which a generating set is capable of delivering while supplying a variable or continuous electrical load and during unlimited run hours. Depending on the sites to supply and the availability of reliable utility, the generating set manufacturer is responsible to define what power level is able to supply to fulfil that requirement including hardware or software or maintenance plan adaptation.

Warranty informations

Standard warranty period:

- for Products in "back-up" service
 - o 30 months from the date the Product leaves the plant
 - o 24 months from the Product's commissioning date
 - o 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
 - $\circ\hspace{0.4cm}$ 18 months from the date the Product leaves the plant
 - $\circ\hspace{0.4cm}$ 12 months from the Product's commissioning date
 - o 2,500 running hours

The warranty expires when one of the above conditions is met. For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".

Standard scope of supply

All our gensets are fitted with:

- Industrial water cooled DIESEL engine
- · Radiator with coolant
- Electric starter & charge alternator 24 V D.C
- Electronic governor
- Standard air filter
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with vibration attenuation mounts
- · Flexible fuel lines & lub oil drain pump
- Exhaust outlet with flexible and flanges
- M80 control panel
- User's manual (1 copy)
- · Packing under plastic film
- Delivered with oil
- Delivered with antifreeze liquid

V01E_T2500-04_2025-11-02 4/6

Industrial Generator Set - T2500



- User language selectable
 Specially researched ergonomics
 High level of equipment availability
 USB and Ethernet ports

- Modbus protocol
 Making it easy to extend the installation
 -Complies with the international standard IEC 61131-3

V01E_T2500-04_2025-11-02 5/6



Dimensions and Weights

Compact version

Overall Size, max., L x W x H, (mm) 6085 x 2355 x 2820

Dry weight (kg) 15500

Tank capacity (L) 0



Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L. Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.

V01E_T2500-04_2025-11-02 6/6

^{*} dimensions and weight without options