



Ratings Range

400/230 V - 50 Hz

Standby kW 440 **kVA** 550

Prime kW 400 kVA 500



Benefits and features

Rehlko premium quality

- · Design offices using the latest technical innovations
- Modern fully certified factories
- · A cutting edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested
- Approved for use with HVO (Hydrotreated Vegetable Oil) according to EN15940

Rehlko premium performances

- · Optimized and certified sound levels
- Reliable power, even in extreme conditions
- · Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- · Robust base frames and high-quality enclosures
- Protection of installations and people
- · Approved in line with the most stringent standards

Engines

- Premium level engines, in-house or from strong partners
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

Alternator

- Provide industry leading motor starting capability
- Made in Europe
- Built with a class H insulation and IP23

Cooling

- A compact and complete solution using a mechanically driven radiator fan
- Designed or optimized by Rehlko
- High temperature and altitude product capacity available

Base frame and enclosure

- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1000 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and connection of the generator
- · Robust design optimized for transportation

General Specifications

Manufacturer	Rehlko
Engine ref.	TAD1346GE
Alternator choices	KH01983T
	KH02215T
Performance class	G3

Voltage (V)	400/230
- ,	380/220
	200/115
	240 TRI
	230 TRI
	415/240
	220/127

Controllers APM403 M80-D Terminal block
Consumption @ 100% load ESP (L/h)* 107
Consumption @ 100% load PRP (L/h)* 98

Emission level

Max. Data Center Continuous (DCC) Rating Same as the Prime Rating below Type of Cooling Radiator


Factory installed enclosures M238 M238-DW

"* Volumetric Fuel consumption is up to 4% higher when using HVO than Diesel Fuel"

Generator sets ratings

		Standby rating		Prime	rating	
	Hz	kWe	kVA	Amps	kWe	kVA
400/230	50	440	550	794	400	500
380/220	50	440	550	836	400	500
200/115	50	440	550	1588	400	500
240 TRI	50	440	550	1323	400	500
230 TRI	50	440	550	1381	400	500
415/240	50	440	550	765	400	500
220/127	50	440	550	1443	400	500

V01E_V0550C2-03_2025-11-02 1/6





Engine Specifications		
Engine brand	VOLVO	
Engine ref.	TAD1346GE*	
Air inlet system	Turbo	
Cylinder configuration	6 - L	
Displacement (I)	12,78	
Bore (mm) x Stroke (mm)	131 x 158	
Compression ratio	17.8 : 1	
Speed 50Hz (RPM)	1500	
Maximum stand-by power at rated RPM (kW)	482	
Governor type	Electronic	
Frequency regulation, no-load to full-load	Isochronous	
Frequency regulation, steady state (%)	+/- 0.25%	
Lubrication System		
Oil Filter Quantity and type****		
Charge Air coolant	Air/Air	
****Rehlko recommends the use of genuine oil and filters.		

Fuel System	
Maximum fuel pump flow (I/h)	110
Max head on fuel return line (m	2,4
fuel)	
Fuel	Diesel Fuel/HVO

^{*} Engine reference may be partially modified depending on genset application, options selected by the customer and lead time required.

Consumption with cooling system	
Fuel consumption @ ESP Max Power (I/h)	108,3
Fuel consumption @ PRP Max Power (I/h)	98,6
Fuel consumption @ 75% of PRP Power (I/h)	76,7
Fuel consumption @ 50% of PRP Power (I/h)	51,4
Cooling system	
Radiator & Engine capacity (I)	48
Fan power 50Hz (kW)	12
Fan air flow w/o restriction (m3/s)	6,4
Available restriction on air flow (mm H2O)	20
Type of coolant	Glycol-Ethylene
Radiated heat to ambiant (kW)	17
Heat rejection to coolant HT (kW)	154
Coolant capacity HT, engine only (I)	20
Max coolant temperature, Shutdown (°C)	107
Max. pressure at inlet of HT water pump (mbar)	1100
Thermostat begin of opening HT (°C)	82
Thermostat end of opening HT (°C)	92

V01E_V0550C2-03_2025-11-02 2 / 6

Industrial Generator Set - V550C2



Exhaust system	
Heat rejection to exhaust (kW)	310
Exhaust gas temperature @ ESP (°C)	449
Exhaust gas flow @ ESP (I/s)	1322
Electrical system	
Battery voltage (V)	24
Air Intake system	
Combustion air flow (I/s)	540
Radiated heat to ambiant (kW)	17

Alternator Specifications	
Number of pole	4
Technology	Brushless
AVR Regulation	Yes
Insulation class	Н
Indication of protection	IP23
Number of bearing	1
Number of wires	12
Coupling	Direct
Overspeed (rpm)	2250
Voltage regulation at established rating (+/- %)	0,5
Unbalanced load acceptance ratio (%)	8

Alternator standard features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof constructio
- Superior voltage waveform

Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.

V01E_V0550C2-03_2025-11-02 3 / 6





Basic terminal block

It is used as a basic terminal block for connecting a control unit. Offers the following functions:

- emergency stop button
- customer connection terminal block
- CE certified



M80-D controller

The M80-D can be used as a basic terminal block for connecting a control unit and as an instrument panel with a highly intuitive LCD screen giving an overview of your generating set's basic parameters:

- · Oil gauge
- · Coolant temperature
- Oil temperature
- Engine speed
- Battery voltage
- Charge air temperature
- Fuel consumption, etc.

The engine main functions can be controlled and events are recorded to facilitate diagnostics:

- Starting
- Speed adjustment
- Stopping
- Droop, etc.



APM403 controller

The APM403 is a versatile control unit which allows operation in manual or automatic mode

- Measurements : voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional : Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.
- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 genset events.
- Mains and genset protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G
- Websupervisor, SMS, E-mails

Codes and Standards

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

Power ratings definition according to ISO8528-1

(2018-02 edition) and ISO-3046-1

Emergency Standby Power (ESP): The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <70%.

Prime Power (PRP): At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <70%.

Warranty informations

Standard warranty period:

- for Products in "back-up" service
 - o 30 months from the date the Product leaves the plant
 - o 24 months from the Product's commissioning date
 - o 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
 - o 18 months from the date the Product leaves the plant
 - 12 months from the Product's commissioning date
 - o 2,500 running hours

The warranty expires when one of the above conditions is met. For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".

Standard scope of supply

All our gensets are fitted with:

- Industrial water cooled DIESEL engine
- Electric starter & charge alternator
- Standard air filter
- Schneider or ABB electric circuit breaker, adapted to the shortcircuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- 4 lifting points on the chassis, lifting bar on the top included from 165 kVA ESP or optional
- · highly durable QUALICOAT certified epoxy paint
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- IP 64 locks, made from stainless materials
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 110 kVA ESP
- · Charged DC starting battery with electrolyte
- · Emergency stop button on the outside
- · Flexible fuel lines & lub oil drain cock
- Exhaust outlet with flexible and flangesUser's manual (1 copy)

Industrial Generator Set - V550C2



- Packing under plastic filmDelivered with oil and antifreeze liquid

V01E_V0550C2-03_2025-11-02 5/6



Dimensions and Weights

Compact version	
Overall Size, max., L x W x H, (mm)	3340 x 1496 x 1742
Dry weight (kg)	3340
Tank capacity (L)	600



1560 x 2450



Dimensions DW compact version			
Overall Size, max., L x W x H, (mm)	4919 x 1560 x 2002		
Tank capacity (L)	1760		
Dry weight (kg)	3930		

M238 - Dimensions DW soundproofed version

m200 - Dimensions DW Soundproofed Version			
Overall Size, max., L x W x H, (mm)	4919 x 1560 x 2710		
Tank capacity (L)	1760		
Dry weight (kg)	5110		
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	102		
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	84		
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	74		



Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.

Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.

V01E_V0550C2-03_2025-11-02 6 / 6

^{*} dimensions and weight without options